



- 01 **Slim:** With a sleek, but durable body, the PS Ultra works well in tight spaces
- 02 **Compatible:** Works with all nozzles for easy retrofitting
- 03 **Versatile:** PS Ultra is available in an array of configurations

## PS ULTRA SLIM-LINE SPRAY SPRINKLER

### *PS Ultra Is the Slim Spray with All the Features For Any Installation*

This compact slim-line spray sprinkler comes in 5 cm, 10 cm, and 15 cm models. Its innovative body incorporates a reliable two-piece ratchet, durable cap, male-threaded riser, and large filter screen, providing double filtration on 10 cm and 15 cm models. Additionally, the 5 cm and 10 cm models are retro-compatible with existing PS Spray bodies, which allow for a quick and easy upgrade. Standard PS Ultra models include a pre-installed Pro Adjustable nozzle. A Flush Plug version is available without a nozzle or filter screen. With so many compatible nozzles to choose from, finding the most efficient solution for the right application is simple and easy.

# PS ULTRA FEATURES & SPECIFICATIONS

## Features

- Application: Residential
- Models: 5 cm, 10 cm, 15 cm
- Nozzle choices: 5
- Nozzle choices: 3.0 m, 3.7 m, 4.6 m, 5.2 m, 1.5 x 9.1 m side strip (side strip pattern available on 5 and 10 cm models only)
- Preinstalled Pro Adjustable nozzle
- Enhanced cap for more durability, easier handling, and extended riser seal life
- 5 cm and 10 cm models can retro-fit into older style PS sprays
- Two-piece ratchet
- Male threaded riser to accept all female nozzles
- Available with flush plug (large filter screen not included)
- Extra large filter screen
- Warranty period: 2 years

## Specifications

- Flow: 0.04 to 1.22 m<sup>3</sup>/hr
- Radius: 2.5 to 9.1 m
- Recommended pressure range: 1.4 to 4.8 bar; 140 to 480 kPa
- Precipitation rates: 43 mm/hr approx.

### PS ULTRA - SPECIFICATION BUILDER: ORDER 1 + 2

1 Models	2 Radius
<b>PSU-02</b> = 5 cm (2") Pop-up	<b>(blank)</b> = No option
<b>PSU-04</b> = 10 cm (4") Pop-up	<b>10A</b> = 3.0 m (10') Adjustable nozzle
<b>PSU-06</b> = 15 cm (6") Pop-up	<b>12A</b> = 3.7 m (12') Adjustable nozzle
	<b>15A</b> = 4.6 m (15') Adjustable nozzle
	<b>17A</b> = 5.2 m (17') Adjustable nozzle
	<b>5SS</b> = 1.5 m x 9.0 m Side Strip (2" and 4" only)

#### Examples:

- PSU-04 - 15A** = 10 cm pop-up, with a 4.6 m adjustable nozzle  
**PSU-02 - 5SS** = 5 cm pop-up, with a 1.5 m x 9.0 m side strip  
**PSU-06 - 10A** = 15 cm pop-up, with a 3.0 m adjustable nozzle

## Models

In addition to our standard models with a pre-installed Pro Adjustable nozzle, a Flush Plug version is available without a nozzle or filter screen.



### [A] PSU02

Overall Height: 12.7 cm  
Pop-up Height: 5 cm  
Exposed Diameter: 3 cm  
Inlet Size: ½"

### [B] PSU04

Overall Height: 8.4 cm  
Pop-up Height: 10 cm  
Exposed Diameter: 3 cm  
Inlet Size: ½"

### [C] PSU06

Overall Height: 24.1 cm  
Pop-up Height: 15 cm  
Exposed Diameter: 3 cm  
Inlet Size: ½"

**Website** [hunterindustries.com.au](http://hunterindustries.com.au) | **Customer Support** +1 760-744-5240 | **Technical Service** +1 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

  
Gregory R. Hunter, President of Hunter Industries